

SPREADERS

TAR RIVER IMPLEMENTS



Web: TarRiverMFG.com
Email: Sales@TarRiverMFG.com
Info@TarRiverMFG.com


DISTRIBUTED BY: **BELCO** 
RESOURCES
EQUIPMENT

401 Jeffreys Road
Rocky Mount, NC 27804
Tel: (252) 822-7140
Web: www.BR-Equipment.com
Email: Sales@BR-Equipment.com



PULL-TYPE (PTS SERIES)

- Heavy duty steel gears in gearbox
- Adjustable towing hitch
- High floatation tires
- Powder coated frame and hopper or Poly hopper
- Left – center – right spread pattern
- Optional spread deflector shield available
- 13” x 6” Tires on PTS -100
- 16 1/2” x 8” on PTS-160



Optional Deflector
Shield

Model	Capacity lbs.	Capacity – Cu. Ft.	Spread Swath	Hopper	Hopper Height	Tires	Wt. lbs.
PTS-100	225	3.7	20’	Metal	40’	13” x 6”	75
PTS-100P	225	3.7	20’	Poly	40’	13” x 6”	70
PTS-160	360	5.3	20’	Metal	44’	16 1/2” x 8”	82
PTS-160P	360	5.3	20’	Poly	44’	16 1/2” x 8”	76



THREE-POINT HITCH—STEEL (SSS SERIES)

- Cat.1 three point hitch
- Dependable Gearbox
- Fixed Agitator (Optional Roller Wheel Agitator)
- Sturdy Metal Hopper With Special Heat-Treated Paint To Resist Rust

Model	Capacity lbs.	Capacity Cu. Ft	Hopper Height	Spread Swath	Weight lbs.
SSS-300	716	11.5	40”	46’	115
SSS-500	1,058	17	46”	46’	133

SUB-COMPACT—POLY (SSC & SP SERIES)

- Low Profile Hopper Height
- Cat.1 three point hitch
- Dependable Gearbox
- Fixed Agitator
- Poly hopper



Model	Capacity lbs.	Capacity —	Hopper Height	Spread Swath	Weight lbs.
SSC-100	224	3.6	31”	23’	83
SP-300SS	716	11.5	42”	46’	127
SP-500SS	1,121	17	46”	46’	135



PENDULAR (SPTO SERIES)

- Ideal for medium tractor power
- Great for spreading seed, salt, sand, and gravel.
- Poly Hopper with Painted Frame
- Stirrer Standard
- Flywheel Protection
- Cat 1&2 Hitch

Model	Unit Dimensions	Max Capacity	Spread Swath		Wt. Lbs.
SPTO-350	45" x 46.5" (dia.)	795 lbs.	39' - 46' Granulated	16' - 19' Powdered	203

COMPACT SIDE-SHOT (SR SERIES)



- Designed for spreading fertilizer and salt
- Category 1 & 2 Hitch
- Stainless Steel Bottom
- Material shoots out of both left and right sides
- Standard Grate Filter & Hydraulic Lever Control for Spreader Gate
- Stainless Steel Bottom




Standard Grate Filter

Standard Hydraulic
Lever Control for
Spreader Gate



Model	Max Capacity	Spread Swath	Unit Dimensions (H x W)	Weight
SR-600	1,719 lbs.	26' - 59'	38" x 51"	229 lbs.
SR-800	2,204 lbs.	26' - 59'	40" x 55"	264 lbs.



3 Possible Spread Patterns

PENDULAR (SQTF SERIES)

- Excellent precision & versatile material spread action such as high moisture (up to 30%) & powdered fertilizers
- Category 1&2 hitch
- Stainless steel bottom
- Strong Tubular Frame & Heavy Polyethylene Hopper



OPTIONAL EQUIPMENT




Salt & Sand Chute
Specifically designed for salt and sand!



Agitator Extension
Helps Maintain Consistent Flow by Breaking Down Clumps & Minimizing Compaction



Rubber Chute Insert
For Damp Material



Grate Filter
Helps Keep Clods & Undesirable Particles from Entering the Discharge Chute

Model	Unit Dimensions	Max Capacity	Spread Swath		Wt. Lbs.
SQTF-600	38" x 59" x 59"	1,402 lbs.	39' - 46' Granulated	16' - 19' Powdered	322
SQTF-1000A	47" x 59" x 59"	2,645 lbs.	39' - 46' Granulated	16" - 19" Powdered	344

Optional Equipment

SQTF-001	Salt & Sand Chute
SQTF-002	Rubber Chute Insert
SQTF-004	Agitator Extension
SQTF-005	Grate Filter